



MUSCLE STIMULATOR

MODEL MST100

This board has been designed with a view to provide practical and experimental knowledge of Muscle Stimulator.

SPECIFICATIONS

Galvanic output -0 to 120V DC low ripple

Interrupted Galvanic output

Intensity -0 to 120V Continuously adjustable

Pulse width -0.3, 1, 10, 100 & 300mSec.

Pulse frequency -0.3, 1 & 3, Pulses/Sec.

Faradic Output

Pulses -500microsec. Wide pulses at 100MHz.

Intensity -0 to 50V continuously adjustable

Surge Faradic Output -Output similar to Faradic with contraction Adjustable upto 6sec.

rest period adjustable upto 8sec.

Supply Voltages -230V AC 50Hz.

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.

Sigma Trainers and Kits
E-113, Jai Ambe Nagar,
Near Udgam School,
Thaltej,
AHMEDABAD - 380054.
INDIA.

Phone(O): +91-79-26852427/ 26850829
Phone(F): +91-79-26767512/ 26767648
Fax : +91-79-26840290/ 26840290
Mobile : +91-9824001168
Email : sales@sigmatrainers.com
: sigmatrainers@sify.com
Web : www.sigmatrainers.com

Dealer:-