




QUADRATURE AMPLITUDE SHIFT KEYING (QPSK) TRAINER MODEL- QASK100

This trainer has been designed with a view to provide practical/experimental knowledge of QASK Modulation /Demodulation technique on a Single PCB.



SPECIFICATIONS

1. Power supply requirement : 230V AC, 50 Hz.
2. On Board Modulating Digital Data signal generator to generate any binary input word with Bit clock & Word clock.
Bit Clock Frequency : 80KHz
Word Clock Frequency : 10 KHz
Word Length : 8 Bits.
Data Format : NRZ, (0 degree) I and (90 degree) Q signals.
3. Modulator Type : Balanced Modulator as QASK Modulator
4. Demodulator Type : Balanced Modulator as QASK Demodulator
VCO with 0 degree and 90 degree Signals.
5. All parts are soldered on single PCB with complete circuit diagram Screen-printed in multi-colour.
6. Standard Accessories :
 1. A Training Manual.
 2. Connecting Patch cords.

EXPERIMENTS

1. To study theory of QASK Modulation & Demodulation.
2. To generate QASK signal and demodulate it
3. To observe QASK modulated output by for different input binary codes.

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.

Sigma Trainers and Kits
E-113, Jai Ambe Nagar,
Near Udgam School,
Thaltej,
AHMEDABAD - 380054.
INDIA.

Phone(O): +91-79-26852427/ 26850829
Phone(F): +91-79-26767512/ 26767648
Fax : +91-79-26840290/ 26840290
Mobile : +91-9824001168
Email : sales@sigmatrainers.com
: sigmatrainers@sify.com
Web : www.sigmatrainers.com

Dealer:-