



TDMA TRAINER

MODEL- TDMA100

This trainer has been designed with a view to provide practical and experimental knowledge of TDMA .



SPECIFICATIONS

1. Power supply requirement : 230V AC, 50 Hz.
2. Built in IC based power supply.
3. On Board Two Input signals generators.
Sine/Triangular wave : Frequency 500Hz. - 1 Vpp
Sine/Square wave : Frequency 1Khz - 1 Vpp.
4. On Board Control Pulse signal generator.
Frequency Range : 2 KHz to 128 KHz.
5. Switching Sections : Time-Space-Time Switching (T-S-T)
6. Space Switching Controls : 16 Bit addresses
7. Low Pass Filters : 3.4 KHz cutoff frequency.
8. All parts are soldered on single pin TAGS on single PCB of size 12" x 9" with complete circuit diagram
Screen-printed in multicolour
9. Standard Accessories :
 1. A Training Manual
 2. Connecting Patch cords.

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.

Sigma Trainers and Kits
E-113, Jai Ambe Nagar,
Near Udgam School,
Thaltej,
AHMEDABAD - 380054.
INDIA.

Phone(O): +91-79-26852427/ 26850829
Phone(F): +91-79-26767512/ 26767648
Fax : +91-79-26840290/ 26840290
Mobile : +91-9824001168
Email : sales@sigmatrainers.com
: sigmatrainers@sify.com
Web : www.sigmatrainers.com

Dealer:-